



BRINKMANN



BOSS ON SITE

The EstrichBoy DC 260 is back!

Ready as ever, stronger than ever!

EstrichBoy
DC 260/45
DC 260/55

HARD SHELL HARD CORE

Understated. Unrivalled. Uncompromising.

BRAWN WITH BRAINS

It's back – and it's stronger, better and smarter than ever before: The new EstrichBoy DC 260 compressed-air conveyor excels itself in comparison with its predecessors – a veritable classic among screed pumps.

DC 260

SO EASY TO TRANSPORT

Lightweight:

Only 1 900 kg with feeder and scraper.

Versatile:

Compatible with many towing vehicles.

Stable roadholding:

Good weight distribution with a low machine centre of gravity.

CLEAN AND QUIET

Europe-ready:

All models meet the strict requirements of the Stage V exhaust emission standard.

Quiet through Europe:

Also fulfils stringent noise regulations.

At home in Europe:

Includes licence for use in (partially) enclosed spaces.

EASILY ACCESSIBLE FOR EASY TIME SAVINGS

Easy access for maintenance:

Wide-opening hood.

Easy access for repairs:

Removable rear panel and floor panel.

Easy-to-clean cooler:

Clean cooler quickly and effectively.

Thoughtful design:

Gradients prevent material deposits forming in the air hoses.

Quick-release couplers:

Simplifies cleaning and replacing the top and bottom air hoses.

WHAT MATTERS: ARRIVE QUICKLY

Innovative keypad:

Easy to operate even when wearing gloves.

Colourful LEDs:

Clear signposting.

Perfect placement:

Feeder lifter and air valves in working area.

Logical arrangement:

Pressure gauge for delivery pressure and mixer pressure.

MIXING, COME WHAT MAY

Reverse operation:

Simplifies removal of stuck-on mixes.

Longer service life:

More reliable overload protection of the mixer thanks to pressure-relief valve.

THE NEW ESTRICHBOY GENERATION AT A GLANCE:

- Meets the toughest environmental and noise regulations
- Even more efficient with the BluePower option for longer-lasting machines
- Extensive standard features
- More options to meet all requirements on the construction site
- The hydraulic mixer features reverse running function and overload protection
- Designed for extremely simple and intuitive operation
- All important service points are easy to reach, saving time and in turn servicing costs

FULL POWER STEP BY STEP

Finely tuned:

The engine speed can be adjusted to one of five levels thanks to the BluePower option.

Full view:

The display indicates whether you are currently saving fuel or utilising the maximum power of the EstrichBoy.

STRONG POWER, NO MATTER WHAT

DC 260/45 with 36.4 kW:

for material delivery rates of up to 5.0 m³/h

DC 260/55 with 44.5 kW:

for material delivery rates of up to 5.2 m³/h

BETTER THAN EVER!

The EstrichBoy DC 260 is back –
even better and even more uncompromising



TECHNICAL DATA TO IMPRESS

	DC 260/45	DC 260/45 B	DC 260/45 BS	DC 260/55	DC 260/55 B	DC 260/55 BS
Mixing vessel	260 l (200 l usable volume)					
Delivery rate (theor.)	3.8 m³/h	4.6 m³/h	5 m³/h	4.0 m³/h	4.8 m³/h	5.2 m³/h
Delivery pressure	8 bar					
Compressor	4.35 m³/min			4.8 m³/min		
Drive motor	Diesel, three-cylinder Deutz with turbocharging, 36.4 kW (Stage V)			Diesel, three-cylinder Deutz with turbocharging, 44.5 kW (Stage V)		
Weight (fully refuelled)	1715 kg	1840 kg	1900 kg	1715 kg	1840 kg	1900 kg
Tank capacity	70 l					
Dimensions (L x W x H)	5067 x 1525 x 1840 mm	5210 x 1525 x 2526 mm		5067 x 1525 x 1840 mm	5210 x 1525 x 2526 mm	
Filling height	820 mm	400 mm		820 mm	400 mm	
Maximum particle size	16 mm					
Chassis	Braked, manual brake adjustment, approved for speeds up to 80 km/h / option to expand to 100 km/h					
Mixer	Hydraulically driven, incl. reverse running and overload protection					
Equipment	Basic version	With hydraulic feeder	With hydraulic feeder and scraper	Basic version	With hydraulic feeder	With hydraulic feeder and scraper



BRINKMANN

A brand of the Putzmeister Group

Max-Eyth-Straße 10 · 72631 Aichtal · Germany

Tel. +49 (0) 7127 5990 · Fax +49 (0) 7127 599 743

info@estrichboy.de · www.estrichboy.de



BRINKMANN